





1996 Diminita Roadster

GENERAL

VEHICLE TYPE: Two-door, two-seater, mid-engined open car, openable hard top with housing on the engine cover, 4WD

DIMENSIONS

EXTERIOR:	
Wheelbase	104.3 inches
Length	178.8 inches
Width	80.3 inches
Height	44.6 inches
Ground Clearance	5.5 inches
Weight	3582 lbs. (w/fluids)
Weight Distribution, front to rear (%)	47/53
INTERIOR:	
Head Room (top on)	37.3 inches
Leg Room	40.3 inches
Shoulder Room	59.4 inches
Hip Room	31.5 inches



CHASSIS

FRAME: Rectangular tubes in high strength steel alloy and carbon fiber composite material.

BODY: Aluminum alloy and hand lay-up composite materials.

Suspension: Independent front and rear double wishbones, coil springs, anti-roll bar.

BRAKE SYSTEM: Power Vacuum H system, Aluminum alloy calipers, ventilated discs:

 Front disc size:
 12.8 x 1.3 in.

 Rear disc size:
 12.4 x 1.1 in.

STEERING: Power assisted rack and pinion: curb to curb turning diameter 511.8 inches.

TIRES: 235/40 ZR 17
Rear 334/35 ZR 17
WHEELS: Aluminum Alloy

 Front
 8.5 x 17 inches

 Rear
 13 x 17 inches

PERFORMANCE

4.0 seconds
14 mpg
9 mpg

ENGINE

V12 guad value DOHC aluminum construction, mid-longitudinal		
Displacement	5.7 liters	
Bore & Stroke	3.43 x 3.15 inches	
Compression Ratio	10.0:1	
Maximum Horsepower	492 SAE @ 7000 RPM	
Maximum Torque	428 lb/ft @ 5200 RPM	
Fuel Requirement	Premium unleaded fuel	

DRIVETRAIN

Transmission Clutch		5 speed manual
		dry single plate 10"
Gear Ratios:		
1st	1:2.31	(60.3 mph)
2nd	1:1.52	. (91.6 mph)
3rd	1:1.12	(124.1 mph)
4th	1:0.88	(158.0 mph)
5th	1:0.68	(200.3 mph)
Reverse	1:2.12	(65.5 mph)
Differential:		

Front - Bevel Gear Type - limited slip 25% - ratio 1:2.81 Rear - Bevel Gear Type - limited slip 45% - ratio 1:2.41 Central Differential - Viscous Coupling

CAPACITIES

13.8 quarts
26 US gallons
15.9 quarts
5.3 cubic feet



(All specifications are subject to change without notice.)

